

tesa® 61002 PV1

Product Information



56 μ m PCR-PET tape for Electrical Insulation applications

Product Description

tesa® 61002 PV1 is a 56 μm blue PCR-PET tape with a water-based acrylic adhesive. tesa® 61002 was designed for electrical insulation applications.

Product Features

- Dielectric breakdown and leakage current protection
- Anti-Repulsion performance
- Reworkability

Application Fields

- Cell-Wrapping
- Metal-Part Insulation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

BackingPost-consumer recycled content of backing	PET film 70 %	Total thicknessResidual water content	56 μm 0.5 g/m²
Type of adhesive	water-based acrylic		
Properties/Performance Values			
 Elongation at break 	80 %	CTI (adhesive side)	600 V
Tensile strength	50 N/cm	 CTI (backing side) 	400 V

Tensile strength 50 N/cm · CTI (backing side) Breakdown voltage 6 KV

Adhesion to Values

Steel 3.2 N/cm



tesa® 61002 PV1

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 26/04/24 – en-US