



tesa[®] 5495 Insulating Tape LA

Product Information

tesa[®] Insulating tape

Product Description

tesa[®] 5489 insulation tape is a PVC tape, with good flexibility and adhesive performance. The tesaflex 5489 tape is certified according to the relevant standards and can be easily used.

Product Features

Backing on thick material (125 µm).
High voltage resistance (4,500 V)

Application Fields

*Useful for insulation and marking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | soft PVC | • Total thickness | 150 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|------------------------------------------------|-------------------------------|-----------------------------|
| • Tensile strength | 32 N/cm | • Suitable surfaces | Steel, Metal, Most plastics |
| • Abrasion resistance | no | • Temperature resistance | yes |
| • Adhesive strength | Standard adhesion | • Temperature resistance max. | 90 °C |
| • Applicationfield | Home, Garden,
Garage, Roof, Car,
Ceiling | • Tensibility | 260 % |
| • Batteries included | no | • UV resistant | no |
| • Batteries required | no | • Waterproof | no |
| • Oil and grease resistance | no | • Writable | no |
| • Residue-free removability | no | | |



tesa[®] 5495 Insulating Tape LA

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=05495>