



# tesa® 52332

## Product Information



300 µm plate mounting tape, permanent bond

### Product Description

tesa® 52332 is a double-sided tape of 300 µm (12 mil) thickness with a PVC backing and an acrylic adhesive. It is designed for demanding plate mounting applications, especially where high adhesion is required and plates are mounted permanently. This is for example the case in corrugated board postprint where plates are commonly mounted to carrier films and hung vertically when stored.

### Product Features

- The structured PP liner prevents the formation of air pockets during plate mounting.

### Application Fields

Plate mounting for various applications, especially for permanent bonds

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                   |                 |    |
|--------------------|-------------------|-----------------|----|
| • Backing          | soft PVC          | • Type of liner | PP |
| • Type of adhesive | tackified acrylic |                 |    |

### Properties/Performance Values

- |                      |     |
|----------------------|-----|
| • Thickness category | 300 |
|----------------------|-----|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=52332>