

tesa® EasySplice 61152 CoaterLine Premium



Product Information

Repulpable flying splice tape

Product Description

tesa® EasySplice 61152 CoaterLine Premium is a repulpable double-sided integrated flying splice tape consisting of a flat-back paper and a modified water soluble acrylic adhesive.

Product Features

- Very high heat resistance
- Good repulpability over full pH-range (pH3 –pH9)
- Very high tack properties
- Very good adhesion values on coated and uncoated paper
- Two blue splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the coating process and for a secure attachment of the tape to the paper roll – no folding back of tape while attaching top sheet
- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Printable and coatable backing
- Low splice thickness

Application Fields

tesa® EasySplice 61152 CoaterLine Premium is particularly suitable for:

- Flying splice applications on off-line coaters

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|------------------------------|
| • Backing | flat paper | • Type of liner | repulpable siliconised paper |
| • Type of adhesive | repulpable tackified acrylic | • Total thickness | 100 µm |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|---------------------------|-----------|
| • Elongation at break | 6 % | • Static shear resistance | good |
| • Tensile strength | 30 N/cm | • Tack | very good |
| • Shelf life time (packed) < 25°C | 16 months | | |

tesa® EasySplice 61152 CoaterLine Premium

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61152>