




tesa[®] 58344

Product Information



tesa[®] 58344

Product Description

is a 90µm single-sided blue PET filmic tape.

The 75µm blue PET backing offers excellent electrical insulation property. The PET liner ensures it can be easily released without adhesive residue and provides good converting ability.

Product Features

- Excellent electrical insulation property.
- Suitable adhesion on metal parts.
- Good convertability
- Halogen-free

Application Fields

- Electrical insulation on metal parts.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------------|
| • Backing | PET | • Total thickness | 90 µm |
| • Type of adhesive | modified acrylic | • Color | blue |
| • Type of liner | PET | • Color of liner | transparent |

Properties/Performance Values

- | | | | |
|--------------------------------|----------|------------------------------------|-----------|
| • Elongation at break | 140 % | • Suitable for die cutting | yes |
| • Tensile strength | 100 N/cm | • Temperature resistance | very good |
| • Dielectric breakdown voltage | 12000 V | • Temperature resistance long term | 125 °C |

Adhesion to Values

- | | | | |
|-----------------------|--------|-------------------|--------|
| • Aluminium (initial) | 5 N/cm | • Steel (initial) | 7 N/cm |
|-----------------------|--------|-------------------|--------|



tesa[®] 58344

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58344>