



tesa® 60295

Product Information

50µm d/s SMT resistant electrically conductive non-woven tape

Product Description

tesa® 60295 is a double sided electrically conductive self adhesive tape. It consists of an electrically conductive non-woven backing and an electrically conductive acrylic adhesive.

Color: Gray

Product Features

- Thickness: 50µm
- Excellent electrical conductivity in XYZ-direction even at high temperature and humidity
- Good adhesion level even at harsh environmental conditions
- Excellent conformability and adjustment to uneven surfaces
- Smooth liner removability even after several times of high temperature processing

Application Fields

- Flexible PCB and modules for shielding and grounding
- Electrostatic discharge applications
- EMC applications, such as grounding and shielding

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|----------------------|----------------|
| • Backing | conductive non-woven | • Color | gray |
| • Type of adhesive | conductive acrylic | • Color of liner | white/red logo |
| • Type of liner | glassine | • Thickness of liner | 70 µm |
| • Total thickness | 50 µm | | |

Properties/Performance Values

- | | | | |
|--|------------------------|-------------------------------------|----------|
| • Contact resistance z-direction (initial) | 0.02 Ohm / square inch | • Surface resistance x-y-direction | 0.2 mOhm |
| • Release of liner | easy | • Temperature resistance short term | 260 °C |
| • Static shear resistance at 40°C | very good | | |

Adhesion to Values

- | | |
|-------------------------|--------|
| • Steel (after 14 days) | 7 N/cm |
|-------------------------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=60295>



tesa[®] 60295

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60295>