

tesa® 50889 SteamGuard



Product Information

High performance masking tape for steam and vapor protection

Product Description

tesa® 50889 SteamGuard combines a strong polyester backing with a powerful acrylic adhesive. The PET layer serves as an excellent barrier against steam and vapor, protecting the surface which the tape is adhered to.

Product Features

- Excellent protection of the surface from vapor and steam
- High transparency for a secure and subtle application
- Secure adhesion to various materials

Application Fields

tesa® 50889 SteamGuard is used in the appliance industry and is especially suited for protecting countertops from the steam and vapor produced by dishwashers and ovens.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing | PET film | • Total thickness | 236 µm |
| • Type of adhesive | modified acrylic | | |

Additional Information

tesa® 50889 is also available as the die cut tesa® 54889.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50889>