
tesa® 64505

Product Information



50µm double sided transfer tape

Product Description

tesa® 64505 is a double-sided self-adhesive transfer tape consisting of a tackified acrylic adhesive.

Product Features

- Very good bonding strength
- Very good shear resistance
- Excellent anti-repulsion property
- Excellent resistance to demanding environmental conditions

Application Fields

- Component mounting
- FPC fixation
- General mounting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Total thickness	50 µm	• Color of liner	white with tesa logo
• Color	transparent		

Properties/Performance Values

• Ageing resistance (UV)	very good	• Static shear resistance at 23°C	very good
• Humidity resistance	very good		

Adhesion to Values

• PC (initial)	6.3 N/cm	• Steel (initial)	5.1 N/cm
• PC (after 14 days)	7.4 N/cm	• Steel (after 14 days)	7 N/cm

For latest information on this product please visit http://l.tesa.com/?ip=64505

tesa® 64505

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=64505