

tesa® 58338 PV1

Product Information

85 µm PET tape for Electrical Insulation applications

Product Description

tesa® 58338 PV1 is a blue 85 μ m PET tape with a water-based acrylic adhesive. tesa® 58338 PV1 has been designed for electrical insulation applications in EV batteries.

Product Features

- Dielectric breakdown and leakage current protection
- Anti-Repulsion performance
- · Optimized for process automation and automated in-line detection
- Reworkability

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PET film	•	Total thickness	85 μm
•	Type of adhesive	water-based acrylic	•	Color of liner	transparent
•	Type of liner	PET film			

Properties/Performance Values

•	Elongation at break	80 %	•	CTI (adhesive side)	600 V
•	Tensile strength	50 N/cm	•	CTI (backing side)	400 V
•	Breakdown voltage	7 KV	•	Liner removal force	40 cN/cm

Adhesion to Values

• Steel 4.5 N/cm





tesa® 58338 PV1

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

