



tesa[®] 4134 Solar

Product Information

Transparent, PP/Acrylic tape

Product Description

tesa[®] 4134 Solar is based on a PP backing with a water based acrylic adhesive.

Product Features

- Especially transparent and clear
- High adhesion
- Excellent aging resistance
- Easy dispensing without curling
- Acid and solvent free
- Environmentally compatible PP-foil

Application Fields

tesa[®] 4134 Solar holds the cells in place during the lamination process.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 50 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------|-----|
| • Elongation at break | 90 % | • Automatic application | yes |
| • Tensile strength | 27 N/cm | • Manual application | yes |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.5 N/cm |
|---------|----------|



tesa[®] 4134 Solar

Product Information

Additional Information

High temperature resistance up to 150°C (short term)

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04134>