



tesa® 4441

Product Information



Cinta de empalme de una sola cara repulpable

Product Description

tesa® 4441 es una cinta repulpable de una sola cara sin soporte, compuesta por un papel ligeramente crepado y un adhesivo acrílico modificado soluble en agua.

Colores: Azul claro, Blanco

Product Features

- Excelentes propiedades de estiramiento
- Alta resistencia al cizallamiento
- Muy buenos valores de adhesión en papel estucado y no estucado
- Buena repulpabilidad en todo el rango de pH (pH 3-pH 9)
- Muy alta adherencia
- Papel procedente de bosques certificados y otras fuentes controladas

Application Fields

tesa® 4441 es un producto versátil que se puede utilizar en la mayoría de los tipos de papel. Es especialmente adecuado para:

- Aplicaciones finales de bobina
- Aplicaciones de propósito general

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|---------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 140 µm |
| • Type of adhesive | repulpable tackified acrylic | • Thickness of tape | 140 µm |
| • Type of liner | none | | |

Properties/Performance Values

- | | | | |
|---------------------------|---------|--------------------------------|---------|
| • Elongation at break | 11 % | • Tack | good |
| • Tensile strength | 75 N/cm | • Tensile strength (crosswise) | 36 N/cm |
| • Static shear resistance | good | | |

For latest information on this product please visit <http://l.tesa.com/?ip=04441>



tesa® 4441

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04441>