



tesa® 68592

Product Information

50µm double sided transparent film tape

Product Description

tesa® 68592 is a transparent, double-sided self-adhesive tape consisting of a PET backing and a tackified acrylic adhesive.

Product Features

- Thickness: 50µm
- High bonding strength
- High resistance to demanding environmental conditions
- Good handling performance in converting processes

Application Fields

tesa® 68592 is used for general mounting and laminating applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PET film	• Color	transparent
• Type of adhesive	tackified acrylic	• Color of liner	brown
• Type of liner	glassine	• Thickness of liner	69 µm
• Total thickness	50 µm	• Weight of liner	80 g/m ²

Properties/Performance Values

• Elongation at break	50 %	• Static shear resistance at 23°C	good
• Tensile strength	20 N/cm	• Temperature resistance long term	100 °C
• Ageing resistance (UV)	very good	• Temperature resistance short term	200 °C
• Humidity resistance	very good		

Adhesion to Values

• ABS (initial)	7 N/cm	• Glass (after 14 days)	9.4 N/cm
• ABS (after 14 days)	8.6 N/cm	• PC (initial)	7.9 N/cm
• Aluminium (initial)	6 N/cm	• PC (after 14 days)	9.9 N/cm
• Aluminium (after 14 days)	9.9 N/cm	• Steel (initial)	7.3 N/cm
• Glass (initial)	8.2 N/cm	• Steel (after 14 days)	10.9 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=68592>



tesa® 68592

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=68592>