



tesa[®] PRO 66728 Mounting ACXplus MP

Product Information

Professional, durable tape - Ideal for indoor usage - Industrial quality - Dust and moisture protection

Product Description

Our newest addition to the mounting range: The tesa PRO Mounting ACX^{plus} MP offers adhesion on industrial quality level for indoor applications based on acrylic foam technology. The sealing function of this tape protects against dust and moisture and seals the area between surface and object for a clean hook up. As it compensates irregular areas with its high-level solution, it is a true multi-purpose mounting tape that simplifies a craftsman's and -woman's daily work. Its viscoelastic behaviour ensures secure and lasting bonds. The powerful tape adheres to various materials with different surface characteristics, satisfying you and your customers. It is resistant to damage caused by moisture, (certain) chemicals, softening agents and UV-lights. This high-performance industrial tape is just what your toolbox needs. tesa - more than just a tape

Product Features

Easy to apply:

- In order for the mounting tape to develop its full holding power, the object and surface must be free of dust, dirt and grease.
- Don't touch the open adhesive surface as it could impair the adhesive strength.
- Apply in vertical strips and along the full length of the object or surface.
- Press down firmly on the mounting tape for at least five seconds.
- As the mounting tapes are intended for permanent use, material residues may remain on the object. Try to remove with tesa adhesive remover.

Application Fields

- Industrial quality: top-level tape with innovative acrylic foam, resistant to damage caused by moisture, (certain) chemicals, softening agents and UV-light
- Sealing function: the professional solution seals and protects against dust and moisture - fills gaps on surfaces of various materials with different characteristics
- Ideal for interior use: Strong double-sided adhesive tape for secure fixing of flat objects such as signs and more
- Easy to use: The mounting tape can be cut into individual small or large pieces for an adhesive strip in the optimized size

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|-------------------|--------|
| • Backing | foamed acrylic | • Total thickness | 800 µm |
| • Type of adhesive | foamed acrylic blend | | |

For latest information on this product please visit <http://l.tesa.com/?ip=66728>



tesa[®] PRO 66728 Mounting ACXplus MP

Product Information

Properties/Performance Values

- | | | | |
|--------------------------|-----------|-----------------------|------|
| • Ageing resistance (UV) | very good | • Humidity resistance | good |
| • Chemical Resistance | good | | |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=66728>