



tesa[®] Professional, tesa[®] 65538PRO Anti-slip Black/Yellow



Product Information

Anti Slip tape - black / yellow

Product Description

tesa[®] 60951 is an anti slip adhesive tape with a wide range of possible applications. The anti slip tape comprises a PVC substrate coated with aluminium oxide. tesa[®] 60951 is the black/yellow version of the product.

Product Features

- The strong adhesive mass of acrylate ensures safe footing on the underlying surface.
- The particularly abrasion-resistant and resilient adhesive tape is impervious to chemicals and salt water
- It can be torn by hand and removed again without any difficulties.
- It is certified in accordance with DIN 51130
- The anti slip effect lasts for up to two years with ordinary use.

Application Fields

- Indoor and outdoor applications
- Applications in which a secure grip underfoot is required
- Black-yellow (tesa[®] 60951): marking of very slippery surfaces
- Transparent (tesa[®] 60952): make valuable surfaces such as wooden stairs, for example, safe unobtrusively
- Fluorescent (tesa[®] 60953): stays bright for a long period for safety and warning purposes in dark rooms

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--|----------------------|--------|
| • Backing | PVC film coated with mineral particles | • Color of liner | yellow |
| • Type of adhesive | acrylic | • Thickness of liner | 180 µm |
| • Total thickness | 900 µm | • Thickness of tape | 720 µm |



tesa[®] Professional, tesa[®] 65538PRO Anti-slip Black/Yellow

Product Information

Properties/Performance Values

• Elongation at break	25 %	• Easy to write on	no
• Tensile strength	30 N/cm	• Fluorescent	no
• Abrasion resistance	very good	• Hand tearability	good
• Ageing resistance (UV)	good	• Humidity resistance	very good
• Batteries included	no	• Softener resistance	good
• Batteries required	no	• Suitable for die cutting	yes
• Chemical Resistance	good	• Temperature resistance long term	50 °C
• Easy to remove	no	• Water resistance	good

Adhesion to Values

• Steel	5.8 N/cm
---------	----------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=NaN>