



tesa® Professional 4665 Outdoor Transparent Cloth Tape



Product Information

Clear cloth tape for outdoor applications

Product Description

tesa® 4665 is a clear cloth tape that was specially developed for outdoor use. The outdoor adhesive tape has a neutral odour and comprises a substrate of PE-extruded fabric and a synthetic rubber adhesive mass. It is a valuable aid when carrying out challenging DIY jobs.

Product Features

- Thanks to its robust design, the superior tesa® adhesive quality and its resistance to UV light and weather conditions, it can be used for up to a year after its initial application.
- The clear cloth tape can be torn by hand and is easy to use.

Application Fields

- Longterm outdoor applications (up to 1 year)
- Heavy duty packaging of outdoor exposed goods
- Quick repairs and seals
- Patching of hosepipes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing | PE extruded cloth | • Total thickness | 215 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|------|
| • Elongation at break | 27 % | • Hand tearability | good |
| • Tensile strength | 43 N/cm | • Water resistance | good |
| • Abrasion resistance | good | | |



tesa® Professional 4665 Outdoor Transparent Cloth Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04665>