



tesa[®] 60900

Product Information

Butylbond Double Sided Butyl Rubber Tape

Product Description

Sealing subconcrete membranes in critical areas. Sealing grain bunkers. Sealing dam liners. Rubber roofing membranes, corrugated roofing and other applications where a strong, long lasting waterproof seal is required. Instant high tack. High tensile strength. Good moisture resistance. Consistent 1.0mm thickness

Product Features

0

Application Fields

Sealing subconcrete membranes in critical areas. Sealing grain bunkers. Sealing dam liners. Rubber roofing membranes, corrugated roofing and other applications where a strong, long lasting waterproof seal is required. Instant high tack. High tensile strength. Good moisture resistance. Consistent 1.0mm thickness

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------|-----------------|-------------------|---------|
| • Backing | PET-rayon cloth | • Total thickness | 1000 µm |
| • Type of liner | paper | • Color | black |

Properties/Performance Values

- | | | | |
|------------------------------------|---------|-------------------------------------|--------|
| • Tensile strength | 68 N/cm | • Temperature resistance short term | 120 °C |
| • Temperature resistance long term | 30 °C | | |

Adhesion to Values

- | | |
|-------------------|---------|
| • Steel (initial) | 20 N/cm |
|-------------------|---------|



tesa[®] 60900

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60900>