



tesa[®] 4921

Protection tape

Product Information

Film de protección azul

Product Description

La cinta tesa[®] 4921 consiste en un soporte de PE con adhesivo acrílico. Tiene una adherencia suave para la protección temporal de superficies y es fácil de retirar después de su uso, sin desgarrarse ni dejar residuos. El soporte de PE es resistente a la intemperie y permite aplicarla a mano sobre la zona que se desea proteger.

Product Features

- Resistente a la intemperie y a los rayos UV durante 6 meses
- Eliminación limpia
- Translúcido.

Application Fields

- Protección de vidrios de ventanas durante la construcción
- Protección de perfiles de aluminio y PVC

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Type of adhesive | acrylic | • Total thickness | 35 µm |
|--------------------|---------|-------------------|-------|

Product Assortment

- | | | | |
|--------------------|------------------------------|-------------------------|----|
| • Available colors | blue | • Available thicknesses | 35 |
| • Available liners | PE/PP protection film,
PE | | |

Properties/Performance Values

- | | | | |
|-----------------------|-------------------|--------------------------------|---------|
| • Elongation at break | 300 % | • Material of masking coverage | PO film |
| • Tensile strength | 6 N/cm | • Temperature resistance | good |
| • Humidity resistance | medium | • Water resistance | medium |
| • Material | PE (polyethylene) | | |

Adhesion to Values

- | | |
|---------|-----------|
| • Steel | 0.77 N/cm |
|---------|-----------|

For latest information on this product please visit <http://l.tesa.com/?ip=04921>



tesa[®] 4921

Protection tape

Product Information

Storage Conditions

Storage Conditions

El almacenamiento debe realizarse en un ambiente alejado de la luz solar, humedad entre 40 y 70%, temperatura entre 15 y 30°C.

Additional Information

Datos Técnicos

- Material Dorso : Polietileno
- Color: Azul
- Grosor total: 35mic
- Tipo de adhesivo: Acrílico

Adherencia

- Acero: 0,77 N/cm
- Vidrio: 0,8 N/cm
- Acrílico: 1 N/cm
- Policarbonato: 0,9 N/cm

Propiedades

- Resistencia a la tracción: 6 N/cm
- Alargamiento: 300
- Temperatura de aplicación: -5 a 60°C

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04921>