

tesa® PRO 74662 STRONG Duct Tape

Product Information

Professional strong Repairing tape for long-lasting bonds

Product Description

Professional craftsmen need PRO-tools - the tesa PRO STRONG Duct Tape 74662 is a versatile, reliable and high performing repairing tape with extra strong bonding power. Due to its easy tearability and flexibility, this duct tape offers the best allround support for quick solutions during your busy work day. It even repels water and shortly resists high temperatures, suiting it for indoor and outdoor usage. The tape consists of a polyethylene film and a woven polyester fabric backing coated with a synthetic rubber adhesive. Available in various dimensions to fit your individual purpose.

Product Features

- tesa PRO STRONG Duct Tape for professionals of every craft, your general purpose tape that is easy to apply and works even on slightly rough surfaces.
- PRO STRONG Duct Tape is truly reliable for various applications like sealing, repairing, fastening or packaging.
- Based on synthetic rubber, this new PRO STRONG Duct Tape has never been stronger while still being easy to unwind and convenient to tear. Use indoors or outdoors.
- A must-have for every craftsmen toolbox: This Duct Tape is for temporary and permanent applications, the perfect allround support with superior tesa quality.

Application Fields

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------------|-------------------|--------|
| • Backing | PE-film with PET-filament | • Total thickness | 215 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----------|-----------------------------|------|
| • Elongation at break | 19 % | • Residue-free removability | no |
| • Tensile strength | 40 N/cm | • Solvent free | yes |
| • Abrasion resistance | good | • Tear resistance | yes |
| • Hand tearability | very good | • Water resistance | good |

Adhesion to Values

- | | |
|------------------|----------|
| • Rough surfaces | 6.5 N/cm |
|------------------|----------|

tesa® PRO 74662 STRONG Duct Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=56388PRO>