

tesa® Professional 4498

Easy Cover Facade Protection

Product Information

tesa® 4498 Easy Cover

Product Description

The tesa® Easy Cover Facade Protection is the effortless way to protect facade and sensitive parts of walls or houses during plastering or painting work. The film added to the reliable cloth adhesive tape makes sure that no paint can leak or bleed into the protected areas. That way, you can work without any worries.

With its ease of use, you can fit the tape into most areas that need protection. The natural rubber adhesive provides the grip to hold fast to many surfaces. Moreover, the choice of various widths of tapes allows you to pick which tape is best suited for which area, giving you ideal coverage.

The plastering tape resists UV radiation for 10 days, so you have a good timespan to complete your work in. With the added benefit of the transparent film, you get a solid basis for any plastering or painting task.

Product Features

- Robust cloth tape combined with a thin film that prevents paint bleeding or leaking
- Effortless and quick to remove
- 2-in-1 solution for plastering or painting work
- Residue-free for 10 days
- Applicable on door or window frames as well as a variety of sensitive surfaces
- The sun is no problem with UV resistance for 10 days (1.5 weeks) * Tape composition: backing material = cloth, adhesive = synthetic rubber
- Available sizes: 20m x 550mm, 20m x 400mm, 17m x 2600mm

tesa® Professional 4498

Easy Cover Facade Protection

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 260 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------------------|------|
| • Elongation at break | 20 % | • Material of masking coverage | LDPE |
| • Tensile strength | 55 N/cm | • Suitable for rough surfaces | good |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 5 N/cm |
|---------|--------|

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4498PRO>