

tesa® Professional 66001 sPVC Plastering Tape

Product Information

Robust sPVC Plastering tape

Product Description

A good plastering tape should come in handy for more than just masking. The tesa® sPVC Plastering Tape also offers the adhesive strength and sturdy build that allows you to tape items into place as well as bundle them together, for example to keep these sorted and available for later use.

For all those uses, the tape offers good weather resistance as it continues its adhesive strength under a variety of temperatures, ranging from average spring/fall temperatures (+5 °C and above) to summer heat with extreme sunshine (+60 °C). Along with the UV resistance for up to six weeks, the plastering tape is well suited to last for as long as your work requires it to stay in place.

The choice of orange or yellow backing colors add to the practicality of the tape as it can also serve, for instance, to mark different applications. The natural rubber adhesive even sticks to slightly rough surfaces, such as a number of facade options. With that, the tesa® sPVC Plastering Tape is a good addition to any tool kit.

Product Features

- Robust sPVC backing combined with powerful natural rubber adhesive allow items to be bundled together or fixed into place
- Adhesive creates good grip on a variety of surfaces, even on slightly rough ones
- Wide temperature range for application, from +5 °C to +60° C
- Residue-free UV resistance for up to six weeks
- Orange or yellow tapes available
- Usable in many environments
- Tape composition: backing material = sPVC, adhesive = natural rubber
- Available sizes: 33m:30mm, 33m:50mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | soft PVC | • Total thickness | 120 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|--------------------|------|
| • Tensile strength | 22 N/cm | • Hand tearability | good |
|--------------------|---------|--------------------|------|

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|

tesa® Professional 66001 sPVC Plastering Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=66001PRO>