

tesa® NOOBLESSE Roll Holder, Self-Adhesive

Product Information

BNR 40479

Product Description

The superb round style of the tesa® Nooblesse roll holder with lid is enhanced by its stainless-steel look. The holder is attached with a formidable adhesive solution rather than drilling. Walls and tiles stay as they were. You can remove the holder without a trace and reuse it elsewhere with a new adapter BK20.

Product Features

- Stable roll holder with lid, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- Superb design, round style, stainless-steel look, circular wall plate
- · Reliable hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- · Can be taken down without a trace or surface damage and re-attached with adapter BK20
- Clean, simple mounting without drilling
- · Soft close function of main hinge, not lid
- Product dimensions: 140mm x 138mm x 52mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	Silane modified	•	Hook shape	Round
		polymer	•	Special features	Soft close
•	Holding power up to	6 Kg			

Properties/Performance Values

•	Applicationfield	Bathroom	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	yes
•	Batteries included	no	•	Reusable with	Adapter BK20
•	Batteries required	no	•	Shape of wall piece	Round
•	Chemical Resistance	no	•	Solvent free	yes
•	Curing time	12 hour(s)	•	Suitable surfaces	Glazed Tiles, Marble,
•	Design series	tesa® NOOBLESSE			Glass, Metal, Stone,
•	Lid	With lid			Concrete, Even wood,
•	Material	Metal			Most plastics
				IIV/ registerst	

UV resistant yesWaterproof yes



tesa® NOOBLESSE Roll Holder, Self-Adhesive

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

