



tesapack[®] Eco & Ultra Strong ecoLogo



Product Information

BNR 58297, 58299

Product Description

Strong tesapack[®] packing tape - Very good adhesion, even on recyclable cartons. Suitable for parcels weighing up to 30 kg. As a contribution to sustainability, the backing material is from 70% recycled PET plastic bottles.

Product Features

- Product with sustainable contribution: The backing material is made of 70% recycled PET bottles
- Reliable: Strong adhesion for securely sealing packages weighing up to 30 kg
- Secure packing: High adhesive strength and tear resistance ensure safe packaging
- Carefree parcel tape: Made without solvents
- Practical: Easily and silently unroll the tape by hand or with the help of a dispenser
- Recyclability tested using the INGEDE method 12: Does not impact cardboard processing
- Versatile adhesive: Good adhesion to recyclable cardboard boxes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------------|-------------------|-------|
| • Backing | Post consumer recycled PET | • Total thickness | 56 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------------|-----------------------|------------------|
| • Elongation at break | 100 % | • Low noise unwinding | yes |
| • Tensile strength | 60 N/cm | • Solvent free | yes |
| • Adhesive strength | High adhesion | • Suitable surfaces | Cardboard, Paper |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Applicationfield | Home, Office | • Unwind force | 5 N/cm |
| • Hand tearability | no | | |



tesapack[®] Eco & Ultra Strong ecoLogo

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>