

tesa[®] 4334 Precision Mask[®]

Product Information

High grade paint tape for precise and flat paint edges

Product Description

tesa[®] 4334 Precision Mask[®] ensures precise and razor-sharp paint edges, while being incredibly easy to use. This is made possible by the combination of a special, supple backing and a perfectly balanced acrylic adhesive compound. The tape adheres flush to the surface, preventing paint tears and delivering professional-quality results that will impress your customers. Additionally, the high quality of the tape helps minimize the need for expensive touch-up work. The tesa[®] Precision Mask[®] 4334 is also recommended for masking applications during spray painting, followed by oven drying up to 120°C/30min. Moreover, the tape is made from sustainable paper, further promoting eco-friendly practices in its production. This thin and low elongating backing makes it ideal for two-tone applications, such as creating straight and long lines.

Sustainable Aspects

tesa[®] 4334 Precision Mask[®] is made with paper from well-managed, certified forests and other controlled sources

Product Features

- Indoor masking (up to 6 months)
- Outdoor masking (up to 8 weeks)
- For smooth and slightly textured surfaces
- For high-quality painting and lacquering work
- For spray painting with afterwards oven drying up to 120°C/30 min
- Made with paper sourced from responsibly managed forests and other controlled sources

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing | Washi paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 4 % | • Hand tearability | very good |
| • Tensile strength | 30 N/cm | • Temperature resistance (30 min) | 150 °C |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|

tesa[®] 4334 Precision Mask[®]

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4334>