

# tesa® Extra-Strong Double-Sided Adhesive Tape Permanent (B)



## Product Information

5672, 5681, 5671, 5686, 5670, 5691, 5696, 5690, 5692

## Product Description

tesa® Flooring Tape Extra Strong Hold is a double-sided flooring tape for the reliable fixation of carpets and PVC in indoor and covered outdoor areas.

## Product Features

- Suitable for all carpets and PVC flooring
- Extra-strong double-sided adhesive tape
- Can also be used with underfloor heating and in damp rooms
- Easy to tear by hand

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |        |
|--------------------|-------------------|-------------------|--------|
| • Backing          | cloth             | • Total thickness | 200 µm |
| • Type of adhesive | tackified acrylic |                   |        |

## Properties/Performance Values

- |                       |                    |                             |                    |
|-----------------------|--------------------|-----------------------------|--------------------|
| • Elongation at break | 20 %               | • Material                  | PP (polypropylene) |
| • Tensile strength    | 30 N/cm            | • Residue-free removability | no                 |
| • Adhesive strength   | Very high adhesion | • Solvent free              | yes                |
| • Chemical Resistance | yes                | • Temperature resistance    | good               |
| • Hand tearability    | yes                | • Tensibility               | 20 %               |
| • Humidity resistance | good               |                             |                    |

## Certificates

**Certified according to**  
DIN 18365

# tesa® Extra-Strong Double-Sided Adhesive Tape Permanent (B)

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=64607DIY>