

tesapack[®] Ultra resistant

Product Information



BNR 45902, 45900

Product Features

• Bundling and palletising * Heavy duty carton sealing * Transport securing * Fixing * End-tabbing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

BackingType of adhesive	glassfibre / PET film synthetic rubber	Total thickness	125 μm
Properties/Performance Values			
Tensile strengthAdhesive strength	250 N/cm Very high adhesion	ReusableRoll width max	no 50 mm
 Ageing resistance (UV) Applicationfield 	no Office, Home	Serrated bladeSolvent free	_NULL no
Batteries includedBatteries requiredHand tearability	no no no	Spare part serviceSuitable surfacesTear resistance	no Cardboard yes
Low noise unwindingMaterial	no Fiberglass	Tension controlTransparency	_NULL medium
Max roll lengthResidue-free removability	66 m no	• Writable	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 1 of 1 – as of 02/03/24 – en-US