



tesa® Professional 4451

Easy Cover Precision Standard Spray Painting

Product Information

Surface protection for Airless applications (spray system)

Product Description

tesa® Easy Cover Precision Standard Spray Painting 4451 is the ideal protection solution for painting jobs with paints and lacquers around staircases or skirting boards, for example. Protection is safe and reliable. The masking paper has a length of 25m and a width of 20cm. The tesa Easy Cover 4451 includes two adhesive tapes to effortlessly apply the surface protection without having to use another tape or waste time applying the second tape. This product can also be used to protect railings, window sills, risers or window frames.

Product Features

- Reliable surface protection for spraying work with paints and lacquers
- Ideal for paint jobs on door frames or skirtingboard
- Quickly mask railings, balustrades, window sills or skirtingboard
- Even easier to use with the help of the handle of a paint roller
- Masking width: 20cm
- Two adhesive edges to speed up masking, removing the need to double tape

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|--------|
| • Backing | Washi paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | • Color | orange |

Properties/Performance Values

- | | |
|-------------------------------|------|
| • Suitable for rough surfaces | good |
|-------------------------------|------|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.7 N/cm |
|---------|----------|



tesa[®] Professional 4451

Easy Cover Precision Standard Spray Painting

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04451>