



# tesa<sup>®</sup> 60989

## Product Information



150µm double sided translucent anti-repulsion non-woven tape

## Product Description

tesa<sup>®</sup> 60989 is a 150µm double sided translucent anti-repulsion tape consisting of a non-woven backing and acrylic adhesive

### Features:

- Conformable
- Easily removable liner
- Suitable for permanent applications
- Excellent temperature resistance performance

## Application Fields

### Packaging applications:

- permanent paper mounting which needs anti-repulsion performance in outer box
- mounting on curved substrates

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |           |                   |                     |
|--------------------|-----------|-------------------|---------------------|
| • Backing          | non-woven | • Color           | translucent         |
| • Type of adhesive | acrylic   | • Color of liner  | white/red logo      |
| • Type of liner    | glassine  | • Weight of liner | 80 g/m <sup>2</sup> |
| • Total thickness  | 150000 µm |                   |                     |

## Adhesion to Values

- |                                    |           |                                     |           |
|------------------------------------|-----------|-------------------------------------|-----------|
| • Steel (easy-side, after 14 days) | 12.7 N/cm | • Steel (tight-side, after 14 days) | 12.7 N/cm |
| • Steel (easy-side, initial)       | 10 N/cm   | • Steel (tight-side, initial)       | 10 N/cm   |



# tesa<sup>®</sup> 60989

## Product Information

### Additional Information

Adhesion to Steel (open side, initial, ASTM3300): 7.3N/cm Adhesion to Steel (covered side, initial, ASTM3300): 7.8N/cm Adhesion to Steel (open side, after 14 days, ASTM3300): 11.2N/cm Adhesion to Steel (high tack side, after 14 days, ASTM3300): 11.4N/cm

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60989>