



tesa® 61036

Product Information



rPET cloth tape with advanced acrylic adhesive

Product Description

tesa® 61036 is a rPET cloth wire harness tape with a solvent-free, advanced acrylic adhesive. It is a flag-resistant rPET cloth tape and ensures secure closure. tesa® 61036 provides excellent abrasion protection and withstands high temperatures. Thanks to its acrylic adhesive it is compatible with halgon-free cable jacketing materials and guarantees enhanced durability.

Sustainable Aspects

For more information: <https://www.tesa.com/product-sustainability>



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- PET cloth with 100% recycled content
- High abrasion and temperature resistance
- Flag resistant
- Excellent cable compatibility
- Resistant to ageing • Can withstand environmental influences
- Flame retardant
- Halogen-free
- Tear-resistant
- Constant unwind force

Application Fields

tesa® 61036 is designed for the engine compartment, provides high abrasion protection and ensures secure bundling performance

Properties/Performance Values

• Elongation at break	40 %	• Noise damping (LV312)	Class A
• Tensile strength	275 N/cm	• Temperature resistance max.	150 °C
• Abrasion resistance (10mm mandrel, LV312)	Class D	• Temperature resistance min.	-40 °C
• Abrasion resistance (5mm mandrel, LV312)	Class D	• Unwind force (roll width < 9mm)	11 N/roll (30 m/min)
• Hand tearability	no	• Unwind force (roll width > 9mm)	11 N/roll (30 m/min)

Additional Information

Standard widths: 9, 19, 25, 32 mm

For latest information on this product please visit <http://l.tesa.com/?ip=61036>



tesa® 61036

Product Information

Additional Information

Standard length: 25 m

*Further dimensions are available on request

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=61036>