

tesa® Adhesive nail canvas for tiles & metal 2kg

Product Information

BNR 77768

Product Description

The adjustable adhesive nail is ideally suited to securely mounting canvases, stretcher frames and other items. It can be taken off without a frame and reused with a new adhesive strip.

Product Features

- · Adjustable adhesive nail for smooth and firm surfaces
- Ideal for mounting canvas paintings and stretcher frames
- Holds objects of up to 2kg per nail (4kg for two nails)
- · Easy On & Off: no tools, removable without a trace
- · Reusable with a new adhesive strip

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	 Holding power up to 	2 Kg
•	Holding power of strip up to	2 Kg	 Silicone free 	yes
	/5 6			

Properties/Performance Values

 Application temperature from 	-15 °C	 Residue-free removability 	yes
 Area of use 	Indoor	 Reusable 	yes
 Batteries included 	no	 Reusable with 	Adhesive Strip 3kg
 Batteries required 	no		Tiles
 Chemical Resistance 	no	 Solvent free 	yes
 Hazard material 	no	 Suitable surfaces 	Even wood, Tiles,
 Humidity resistance 	no		Most plastics, Glass,
 Material 	PS (polystyrene)		Acrylic glass, Steel,
 Oil and grease resistance 	no		Metal
 Ozone resistance 	no	 Temperature resistance max. 	35 °C
		 Temperature resistance min. 	5°C
		 UV resistant 	no
		 Waterproof 	no



tesa® Adhesive nail canvas for tiles & metal 2kg

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

