



tesa® Adhesive nail canvas for tiles & metal 2kg

Product Information

BNR 77768

Product Description

The adjustable adhesive nail is ideally suited to securely mounting canvases, stretcher frames and other items. It can be taken off without a frame and reused with a new adhesive strip.

Product Features

- Adjustable adhesive nail for smooth and firm surfaces
- Ideal for mounting canvas paintings and stretcher frames
- Holds objects of up to 2kg per nail (4kg for two nails)
- Easy On & Off: no tools, removable without a trace
- Reusable with a new adhesive strip

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 2 Kg |
|--------------------|------------------|--------------------------------|------|

Properties/Performance Values

- | | | | |
|--------------------------------|------------------|-----------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | no |
| • Chemical Resistance | no | • Residue-free removability | yes |
| • Hazard material | no | • Reusable | yes |
| • Humidity resistance | no | • UV resistant | no |
| • Material | PS (polystyrene) | • Waterproof | no |
| • Oil and grease resistance | no | | |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>