



tesapack[®] Extra Strong

Product Information

BNR 57170, 57171, 58223, 57169, 57108, 57249, 58196, 05050, 57173, 05049

Product Description

tesapack[®] extra strong is a brown or transparent packaging tape made for demanding applications. It combines a highly tear-proof film with strong adhesion.

Product Features

- Highly tear-proof PVC backing
- Natural rubber adhesive ensures high adhesion
- Very good sealing security
- For packaging and bundling of heavy goods
- Even, low-noise unwinding
- Suitable for use in all tesa[®] hand dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 49 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|--------------------|----------------------|-----------|
| • Tensile strength | 75 N/cm | • Roll width max | 50 mm |
| • Adhesive strength | Very high adhesion | • Serrated blade | _NULL |
| • Ageing resistance (UV) | no | • Solvent free | no |
| • Applicationfield | Office, Home | • Spare part service | no |
| • Batteries included | no | • Suitable surfaces | Cardboard |
| • Batteries required | no | • Tear resistance | yes |
| • Hand tearability | no | • Tensibility | 75 % |
| • Low noise unwinding | yes | • Tension control | _NULL |
| • Max roll length | 66 m | • Transparency | good |
| • Residue-free removability | no | • Writable | no |
| • Reusable | no | | |



tesapack[®] Extra Strong

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>