

# tesa® Adhesive Strips for Wallpaper & Plaster 0.5kg



# **Product Information**

**BNR 77770** 

### **Product Description**

Refill pack for the Adhesive Nail for Wallpaper & Plaster 0.5kg. For convenient reuse of the Adhesive Nail. The clever way to hang pictures.

#### **Product Features**

- Strip for reuse\* of the Adhesive Nail for Wallpaper & Plaster 0.5kg
- · For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 0.5kg\*\* per strip
- · Removable without a trace

# **Application Fields**

How to apply – Step by step 1. Ensure the best possible bond by cleaning the surface of dirt and dust with a dust-free cloth.

- 2. The Adhesive Strip for Wallpaper & Plaster should be applied to the rougher surface so, in case of wallpaper or plaster, apply it to the wall, with the blue tab facing the wall. Before using, make sure that your surface is strong enough to take the weight of the object you want to attach.
- 3. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil. By pressing down like this, the flexible polymer chains are activated to form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.
- 4. Now apply the tesa® Adhesive Nail by aligning it on the top edge of the strip, then folding it down. Press down evenly all over the entire nail for at least 5 seconds.
- 5. The tab should be left accessible below the nail for easy removal.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

· Holding power of strip up to

• Type of adhesive synthetic rubber • Holding power up to 0.5 Kg • Total thickness 1350  $\mu m$  • Silicone free yes

0.5 Kg

<sup>\*</sup>Only for use with an Adhesive Nail

<sup>\*\*</sup>For optimal results please read instruction leaflet



# tesa® Adhesive Strips for Wallpaper & Plaster 0.5kg

# **Product Information**

# **Properties/Performance Values**

•	Application temperature from	-15 °C	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	no
•	Batteries included	no	•	Reusable with	_NULL
•	Batteries required	no	•	Solvent free	yes
•	Chemical Resistance	no	•	Suitable surfaces	Wallpaper, Plaster
•	Hazard material	no	•	Temperature resistance max.	35 ℃
•	Humidity resistance	no	•	Temperature resistance min.	5 °C
•	Oil and grease resistance	no	•	UV resistant	no
•	Ozone resistance	no	•	Waterproof	no

# Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

