



tesa[®] Mounting Tape for Brick & Stone 10 kg/m



Product Information

BNR 77748, 77749

Product Description

Mounting Tape for Brick & Stone up to 10kg/m. The weather resistant way to wall-mount on solid surfaces outside.

Product Features

- For solid surfaces like brick & stone indoors & outdoors
- Holds up to 10kg/m*
- For permanent applications
- Ideal for outdoor applications

*For optimal results a max. of 6kg per application/objects is recommended

Application Fields

- How to apply – Step by step
1. Use a brush to get rid of dust and grit from your surface. This will ensure an optimal bond.
 2. Check if the surface or the object is rougher and apply the mounting tape to it.
 3. Apply the mounting tape in vertical strips corresponding to the full length of the object and press down firmly all along the tape for at least 5 seconds.
 4. Remove the protective foil and, being careful not to touch the exposed adhesive area at any time, position the item.
 5. Press down firmly on the item for at least another 5 seconds to get as close a bond as possible.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------------------|---------|
| • Type of adhesive | acrylic | • Holding power of tape up to | 10 KG/M |
| • Total thickness | 1140 µm | | |

Properties/Performance Values

- | | | | |
|--------------------------------|--------|-----------------------------|----------------------------------------------|
| • Application temperature from | -15 °C | • Residue-free removability | no |
| • Chemical Resistance | yes | • Solvent free | no |
| • Humidity resistance | yes | • Suitable surfaces | Tiles, Most plastics,
Glass, Metal, Steel |



tesa[®] Mounting Tape for Brick & Stone

10 kg/m

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>