



# tesa® Ceiling hook for wallpaper and plaster 0.5kg

## Product Information

BNR 77781

## Product Description

To attach decoration such as a mobile without drilling, the ceiling hook for wallpaper & plaster with its revolving hook head is the right choice. It's easy to attach and take off without a trace.

## Product Features

- Ceiling hook for sensitive surfaces (wallpaper & plaster)
- Mounting baby mobiles and other decorative items without drilling
- Holds objects of up to 0.5kg
- Easy On & Off: no tools, removable without a trace
- Reusable with new adhesive strip

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                       |                  |                 |       |
|-----------------------|------------------|-----------------|-------|
| • Type of adhesive    | synthetic rubber | • Hook shape    | Round |
| • Holding power up to | 0.5 Kg           | • Silicone free | yes   |

## Properties/Performance Values

- |                                |                  |                             |     |
|--------------------------------|------------------|-----------------------------|-----|
| • Application temperature from | -15 °C           | • Ozone resistance          | no  |
| • Chemical Resistance          | no               | • Residue-free removability | yes |
| • Hazard material              | no               | • Reusable                  | yes |
| • Humidity resistance          | no               | • Solvent free              | yes |
| • Material                     | PS (polystyrene) | • UV resistant              | no  |
| • Oil and grease resistance    | no               | • Waterproof                | no  |

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>