



tesa[®] Signal Premium

Product Information



BNR 58130, 58131

Product Description

tesa[®] Signal Premium is a highly tear-proof self-adhesive warning and signaling tape designed to permanently mark danger zones or hazardous areas.

Product Features

- Highly tear-proof PVC backing
- Natural rubber adhesive ensures excellent adhesion
- For marking permanent obstacles and hazard areas
- Even, low-noise unwinding
- Colour code according to EU regulation for marking
- Suitable for use in all tesa[®] hand dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 65 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|----------------------|----------------------|-----------------------------|------------------------------|
| • Tensile strength | 60 N/cm | • Low noise unwinding | yes |
| • Adhesive strength | Very high adhesion | • Residue-free removability | no |
| • Applicationfield | Home, Garden, Office | • Solvent free | no |
| • Batteries included | no | • Suitable surfaces | Even wood, Plaster, Concrete |
| • Batteries required | no | | |
| • Hand tearability | no | • Tear resistance | yes |
| • Hazard material | no | • Tensibility | 60 % |
| | | • Writable | no |



tesa[®] Signal Premium

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>