

tesa[®] Professional 4344 Precision Mask[®] Standard

Product Information

High grade paper masking tape for precise and flat paint edges

Product Description

tesa[®] 4344 Precision Mask[®] Standard is crafted with an extra-thin and robust paper backing that is coated with an acrylic adhesive. The tape's backing material, which is made from sustainable paper, is highly equipped and combined with a special adhesive formulation. This unique combination allows for easy removability up to 3 months after indoor application and provides 4 weeks of UV resistance for outdoor usage. As a result, this versatile tape enables multiple working processes to be carried out in just one covering process.

Sustainable Aspects

tesa[®] Precision Mask[®] Standard is made with paper from well-managed, certified forests and other controlled sources

Product Features

- This tape is suitable for almost all indoor paint works
- tesa[®] 4344 Precision Mask[®] Standard is applicable with water-based paints and lacquers and fits even for spatula techniques
- It may be used on a variety of common surfaces such as glass, aluminium, hard-PVC and wood
- It works especially well for indoor applications when a precise paint edge is needed
- Made with paper sourced from responsibly managed forests and other controlled sources

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing | Washi paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 4 % | • Hand tearability | very good |
| • Tensile strength | 30 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.7 N/cm |
|---------|----------|

tesa[®] Professional 4344 Precision Mask[®] Standard

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4344>