tesa® 4296 US PV10



Product Information

tesa® 4296US Premium Strapping tape

Product Description

tesa® 4296 is a heavy-duty strapping tape with one of our strongest tensilized polypropylene backings. The rubber adhesive system provides high initial tack to both polar and non-polar surfaces. The mono-oriented polypropylene backing exhibits superior tensile strength, and low elongation. This allows high performance in heavy-duty bundling, palletizing, and metal coil end-tabbing applications. With effortless dispensing, our tape accommodates both manual and automatic operations.

Product Features

- solvent-free adhesive
- low elongation
- good workability
- premium tensile strength

Application Fields

- Heavy duty bundling
- Temporary fixation
- Heavy duty palletizing, reinforcing, and box closure
- Metal coil end-tabbing
- High abrasion resistance

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	MOPP	• Total thickness	155 µm
• Type of adhesive	synthetic rubber		

Product Assortment

• Available colors	black, transparent

Properties/Performance Values

• Elongation at break	35 %	• Solvent free	yes
• Tensile strength	375 N/cm		

For latest information on this product please visit http://l.tesa.com/?ip=4296US

tesa® 4296 US PV10

Product Information

Adhesion to Values

- Steel 9 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=4296US