

tesa® 64284 EU PV11

Product Information

tesa® 64284EU Standard Strapping Tape

Product Description

tesa® 64284 PV11 is a medium duty strapping tape designed with a high-performance tensilized polypropylene backing and rubber adhesive system. This advanced formulation ensures exceptional initial tack on both polar and non-polar surfaces, making it the preferred choice across diverse applications and industries. The mono-oriented polypropylene backing showcases outstanding tensile strength and minimal elongation, ensuring utmost durability and reliability. With effortless dispensing, our tape accommodates both manual and automatic operations.

Product Features

- · Solvent-free adhesive
- Low elongation
- · Good workability
- · Premium tensile strength
- Better adhesion on rough surfaces compared to PV10

Application Fields

- · Holding of appliance parts
- · Holding and securing of peripherals
- Residue-free removability from a variety of different surfaces without discoloration

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	MOPP	•	Total thickness	115 μm
•	Type of adhesive	synthetic rubber	•	Color	blue

Product Assortment

Available colors light blue, white

Properties/Performance Values

•	Elongation at break	35 %	•	No discoloration	yes
•	Tensile strength	300 N/cm	•	Residue-free removability	yes

Adhesion to Values

• Steel 7 N/cm



tesa® 64284 EU PV11

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

