



tesa® 4375

Product Information



For Sharp, Clean, and Flat Paint Edges

Product Description

tesa® Precision Mask 4375 is a Washi tape which combines a flat paper backing and an acrylic adhesive and is designed for precise masking jobs ensuring sharp, clean and flat paint lines. It is the ideal solution for architectural painting, marine, train and various other fields where quality results are required.

Product Features

- Designed for precise masking jobs ensuring sharp, clean and flat paint lines.
- Easy demasking without tear and residues.
- High temperature resistance up to 150 °C / 0.5 h.
- Outdoor usability up to 15 days.

Application Fields

- Ideal for 2-tone masking applications
- Suitable for use with common paints and lacquers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing | Washi paper | • Total thickness | 95 µm |
| • Type of adhesive | acrylic | | |

Product Assortment

- | | |
|--------------------|------|
| • Available colors | gold |
|--------------------|------|

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 4 % | • Hand tearability | very good |
| • Tensile strength | 36 N/cm | • UV-resistance | 2 weeks |
| • Easy to remove | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.5 N/cm |
|---------|----------|



tesa® 4375

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04375>