



tesa® PRO 74613

Duct Tape >60% Recycled Plastic

Product Information

tesa® PRO Duct Tape (74613) >60% Recycled Plastic - Professional Repair Tape for Long-Lasting Bonds

Product Description

The tesa® PRO Duct Tape (74613) is an essential tool for every craftsperson's toolbox. Designed to provide exceptional bonding power and adaptability, it is ideal for quick, clean, and long-lasting repairs throughout a busy workday. Suitable for both indoor and outdoor use, this tape repels water and withstands various temperature conditions. The tape features a woven polyester fabric backing, along with a synthetic rubber adhesive for optimal adhesion. Its backing contains > 60% post-consumer recycled (PCR) material, with an overall average of 30% PCR content*(excluding packaging). The increased recycled material content of the tape does not compromise performance, ensuring the strength and longevity needed.

*Externally certified by UL2809-2 (ECVP)

Sustainable Aspects

By incorporating > 60% post-consumer recycled (PCR) material into its backing component tesa® PRO Duct Tape (74613) offers an increased recycled material content without compromising performance.

Product Features

- Reliable All-Rounder Tape: Perfect for temporary and permanent applications, offering trusted tesa quality
- Versatile Application: Adheres to slightly rough surfaces, ideal for sealing, repairing and fastening, meeting the needs of every craftsperson regardless of the task
- Convenient Use: Hand-tearable for quick fixes, simplifying on-the-job problem-solving
- Contributing to sustainability: The backing is made from > 60% post-consumer recycled material (PCR)
- Strength and Quality: Strong hold and easy to unwind, suitable for indoor and outdoor use
- Toolbox Essential: A must-have for craftspeople, available in multiple dimensions

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|---|--------------------|--------------------|------------------|
| • Backing | PE laminated cloth | • Type of adhesive | synthetic rubber |
| • Post-consumer recycled content of backing | 63 % | • Total thickness | 175 µm |

For latest information on this product please visit <http://l.tesa.com/?mp=74613>



tesa[®] PRO 74613

Duct Tape >60% Recycled Plastic

Product Information

Properties/Performance Values

• Elongation at break	18 %	• Hand tearability	good
• Tensile strength	41.5 N/cm	• Humidity resistance	yes
• Abrasion resistance	good	• Residue-free removability	no
• Adhesive strength	Standard adhesion	• Solvent free	yes
• Ageing resistance (UV)	medium	• Tear resistance	yes
• Chemical Resistance	medium		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=74613>