

# tesa® Ultra Power Under Water repair tape

**Product Information** 

BNR 56481, 56491

# **Product Description**

The tesa® Ultra Power Under Water adhesive tape offers a reliable hold and protection in various conditions, such as moisture and heat. This makes it ideal for outdoor repairs, on wet surfaces, or underwater.

# **Product Features**

- For fast and easy fixes in wet environments: Great choice for leaks and damages even under water
- · Robust and durable: The extra-thick repair tape provides exceptionally strong adhesive strength
- · Climate-proof resilience: Waterproofness, UV and temperature resistance ensure effective repairs, at all times
- · Resistance and flexibility: The abrasion-resistant repair tape adapts to various shapes and objects
- · Versatile: Ideal for sealing wet or dry holes, cracks, or leaks, both indoors and outdoors
- Available in black and in transparent, for almost invisible repairs.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul> <li>Backing</li> </ul>	PVC film	<ul> <li>Total thickness</li> </ul>	730 μm
<ul> <li>Type of adhesive</li> </ul>	rubber based		
Properties/Performance Values			
Tensile strength	90 N/cm	Residue-free removability	no
Abrasion resistance	yes	Solvent free	no
<ul> <li>Adhesive strength</li> </ul>	Very high adhesion	Suitable surfaces	Most plastics, Steel,
<ul> <li>Ageing resistance (UV)</li> </ul>	yes		Glass, Metal
Area of use	In- and Outdoor	Tear resistance	yes
<ul> <li>Hand tearability</li> </ul>	no	Temperature resistance	yes
<ul> <li>Oil and grease resistance</li> </ul>	yes	UV resistant	very good
Ozone resistance	yes	Waterproof	yes
		Writable	no



# tesa® Ultra Power Under Water repair tape

**Product Information** 

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 26/05/25 – en-US