

tesa® 4182

PV2

Product Information



Product Description

tesa® 4182 PV2 is a PVC film tape with an acrylic adhesive for basic bundling of automotive harnesses used in the passenger compartment of vehicles. The tape is convenient to use due to its constant unwind force, flexible backing, and hand-tearability. It is optimized for manual application.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

| | | | |
|--------------------|----------|-------------------|--------|
| • Backing | PVC film | • Total thickness | 104 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

| | | | |
|---|---------|-----------------------------------|-----------------------|
| • Elongation at break | 250 % | • Temperature resistance max. | 105 °C |
| • Tensile strength | 25 N/cm | • Temperature resistance min. | -25 °C |
| • Abrasion resistance (10mm mandrel, LV312) | Class A | • Unwind force (roll width < 9mm) | 7.5 N/roll (30 m/min) |
| • Abrasion resistance (5mm mandrel, LV312) | Class A | • Unwind force (roll width > 9mm) | 7.5 N/roll (30 m/min) |
| • Noise damping (LV312) | Class A | | |

Adhesion to Values

| | |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4182PV2>