



tesa® Professional 60953 Anti-slip Fluorescent



Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PVC film coated with mineral particles	• Thickness of liner	180 µm
• Type of adhesive	acrylic	• Thickness of tape	720 µm
• Total thickness	900 µm		

Properties/Performance Values

• Elongation at break	25 %	• Fluorescent	yes
• Tensile strength	30 N/cm	• Fogging	low
• Abrasion resistance	very good	• Hand tearability	good
• Ageing resistance (UV)	good	• Humidity resistance	good
• Chemical Resistance	good	• Suitable for die cutting	yes
• Easy to remove	no	• Temperature resistance short term	50 °C
• Easy to write on	no	• Water resistance	good, medium

Adhesion to Values

• Steel	5.8 N/cm
---------	----------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60953>