



tesa® 4024 PV4



Product Information

Universal carton sealing tape

Product Description

tesa® 4024 PV 4 features a PP backing coated with a high tack water based acrylic adhesive. The well balanced tack and high shear resistance of the adhesive secures a good sealing immediately after application.

Product Features

- Low noise unwinding.
- Excellent ageing resistance.
- Perfect for manual tape application.
- The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

Application Fields

Manual sealing of light and medium weight cartons.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | PP film | • Total thickness | 50 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-------------------------|---------|-------------------------|--------------------|
| • Elongation at break | 140 % | • Packaging Weight | Up to 15 kg |
| • Tensile strength | 45 N/cm | • Silent unwinding | yes |
| • Automatic application | no | • Transport Information | Temperature 0-70°C |
| • Manual application | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.5 N/cm |
|---------|----------|



tesa® 4024 PV4

Product Information

Additional Information

On request tesa® 4024 is also available as PV 5 product version with easy but noisy unwinding and ideal for automated application with long rolls or for on-the-top printing.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04024>