



# tesa® 73900

## Product Information

Surface protection tape

### Product Description

Single-sided foam tape

### Product Features

Foam properties:

- Long lasting, constant recovery characteristics

Adhesive properties:

- Medium tack surface characteristics
- Sufficient bonding
- Easy demounting

### Application Fields

tesa® 73900 is designed for surface protection on various materials like steel, aluminum, PU or PET.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                              |                   |        |
|--------------------|------------------------------|-------------------|--------|
| • Backing          | PE foam with film lamination | • Total thickness | 500 µm |
| • Type of adhesive | modified acrylic             | • Color           | red    |
| • Type of liner    | PP                           |                   |        |

### Adhesion to Values

- |                   |          |
|-------------------|----------|
| • Steel (initial) | 3.5 N/cm |
|-------------------|----------|



# tesa® 73900

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=73900>