



tesa®

## Product Information

BNR 04662

### Product Description

Betonband with reliable adhesive strength for multifunctional work, perfect for indoor and outdoor application.

### Product Features

- Suitable for many applications
- Indoor and outdoor
- UV-resistance
- Handtearable
- High durability
- Moisture resistant

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                    |                   |        |
|--------------------|--------------------|-------------------|--------|
| • Backing          | PE laminated cloth | • Total thickness | 230 µm |
| • Type of adhesive | natural rubber     |                   |        |

### Properties/Performance Values

- |                          |                   |                             |         |
|--------------------------|-------------------|-----------------------------|---------|
| • Elongation at break    | 15 %              | • Humidity resistance       | good    |
| • Tensile strength       | 30 N/cm           | • Residue-free removability | no      |
| • Abrasion resistance    | medium            | • Tear resistance           | yes     |
| • Adhesive strength      | Standard adhesion | • UV-resistance             | 2 weeks |
| • Ageing resistance (UV) | good              | • Water resistance          | medium  |
| • Hand tearability       | good              | • Writable                  | yes     |

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>