



tesa® 4317

Product Information



Thin paper masking tape for paint spraying

Product Description

tesa® 4317 is a slightly creped thin masking tape with a natural rubber adhesive mass that ensures even adhesion. Thanks to the flexible substrate material, the thin masking tape is a valuable aid with many types of paint jobs, is watertight and sticks well to paint and fillers. The masking tape resists temperatures of up to 80 °C, is simple to handle, is easy to both tear by hand and to remove after drying.

Product Features

- tesa® 4317 is a flexible masking tape used for spray-painting, painting, and varnishing applications
- The masking tape has excellent holding power on various surfaces
- The tape is suitable for oven-drying with temperatures of up to 80°C
- Ideal for lacquering work
- Good flexibility for curves
- Can be used on painted metal, rubber, glass and chrome parts
- The tape is easy to remove and is hand-tearable

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|--|--------|
| • Backing | slightly-creped paper | • Total sustainable product excl. liners by weight (acc. EN 16785) | 55 % |
| • Type of adhesive | natural rubber | • Total thickness | 140 µm |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 10 % | • Hand tearability | very good |
| • Tensile strength | 38 N/cm | • Temperature resistance (30 min) | 100 °C |
| • Easy to remove | yes | • Temperature resistance (60 min) | 80 °C |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.3 N/cm |
|---------|----------|



tesa® 4317

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04317>