

tesa® Professional 4439

Precision Mask Outdoor 8 Weeks

Product Information

Waterproof masking tape for precise and flat paint edges outdoors

Product Description

The tesa Precision Mask® Outdoor guarantees razor-sharp paint edges for the outdoors. Because the adhesive compound and backing material are not only extremely precise, they are also particularly weatherproof and UV-resistant. This waterproof masking tape comprises a tear-proof, thin special backing which is coated with an acrylate adhesive compound. Thanks to this combination, the waterproof masking tape remains stable for a long time in all weathers. The paper masking tape is a reliable partner for painting work of all kinds and, combined with sound workmanship, will return excellent results.

Product Features

- Outdoor applications
- For long-term applications (up to 8 weeks)
- Flat, sharp edges to paint and lacquer
- For high-quality painting and lacquering work

*The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Thus before using an adhesive tape on a weathered surface we recommend to make a trial application for up to 24 hours.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|--------|
| • Backing | Washi paper | • Total thickness | 100 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 5 % | • Hand tearability | very good |
| • Tensile strength | 35 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|

tesa® Professional 4439

Precision Mask Outdoor 8 Weeks

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4439>