

tesa® Professional 4431

Product Information

Blue masking tape for outdoor paint jobs

Product Description

tesa® 4431 is a low-creped paper tape with an acrylic adhesive. The right choice for all kinds of outdoor paint tasks, be it the garage door or freshening up your balcony railing. You can use any paint with it. The blue masking tape also resists UV radiation for up to one week, allowing you to complete even more difficult paint work. Easy to apply, it comes in several sizes: 50mx50mm, 50mx38mm, 50mx30mm & 50mx25mm. With the blue painters tape, you always get straight and clean edges – the perfect foundation for a great look.

Sustainable Aspects

tesa® 4431 is made with paper from well-managed FSC®-certified forests, recycled materials, and other controlled sources and it meets the FSC® Standards.

The communication of the FSC® certification is strictly limited to sales organizations that are FSC® certified (FSC® C148769).

Product Features

- Blue masking tape – UV resistance up to one week, allowing even extensive work
- Ideal for all sorts of outdoor paint jobs – e.g. fences, siding, garden shed
- Low-creped paper backing, acrylic adhesive
- Available in the following sizes: 50mx50mm, 50mx38mm, 50mx30mm & 50mx25mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 120 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | |
|--------------------|------|
| • Hand tearability | good |
|--------------------|------|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.3 N/cm |
|---------|----------|

tesa® Professional 4431

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=64431PRO>