



# tesa® 68204

## Product Information



400µm double-sided acrylic foam tape

### Product Description

tesa® 68204 is a 400µm double-sided acrylic foam tape in gray color, the AC foam works both as backing and adhesive providing good tack performance even under low operating temperature.

Also available in 640µm, 800µm and 1100µm formats.

### Product Features

- Suitable for low temperature operation
- Good bonding on various substrates
- Cost-effective as entry level standard product

### Application Fields

Example mounting applications include but are not limited to:

- Decorative glass panel mounting
- Plastic panel mounting
- Nameplate and parts mounting
- TV back panel mounting

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	Acrylic foam	• Total thickness	400 µm
• Type of liner	PE-coated paper	• Color	gray

### Product Assortment

• Available liners	PE-coated paper, PE
--------------------	---------------------

### Properties/Performance Values

• Tack	good	• Temperature resistance short term	200 °C
• Temperature resistance long term	100 °C		



# tesa® 68204

## Product Information

### Adhesion to Values

• ABS (initial)	6 N/cm	• Glass (after 3 days)	14 N/cm
• ABS (after 3 days)	9 N/cm	• PC (initial)	9 N/cm
• Aluminium (initial)	10 N/cm	• PC (after 3 days)	11 N/cm
• Aluminium (after 3 days)	14 N/cm	• Steel (initial)	13 N/cm
• Glass (initial)	12 N/cm	• Steel (after 3 days)	20 N/cm

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=68204>